

Serie | 6, Island cooker hood, 90 cm,
Stainless steel
DIB98JQ50B

A+



Optional accessories

- DHZ1231 : Adapter for roof inclination left/right
- DHZ1241 : Adapter for roof inclination front/back
- DHZ1246 : Chimney extension 1100 mm
- DHZ1256 : Chimney extension 1600 mm
- DHZ5346 : Standard odor filter (replacement)
- DHZ5385 : Standard recirculation kit
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6230 : CleanAir Recirculation Kit
- DZZ0XX0P0 : Long Life odor filter (replacement)

Stylish island chimney hoods perfectly complement island hob installations.

- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **PerfectAir sensor:** automatic control of settings for maximum extractor performance with minimal noise.
- **DirectSelect control:** direct selection of desired settings and light.
- **Extra quiet:** maximum extractor performance with minimal noise.
- **High grease filtration level:** filters up to 89.2% of the grease from the kitchen air.

Technical Data

Typology :	Chimney
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	130
Height of the chimney (mm) :	698-878/698-998
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	30.424
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m3/h) :	445
Boost position output recirculating (m3/h) :	391.0
Boost position air extraction (m³/h) :	867
Number of lights (Stck) :	4
Noise level (dB(A) re 1 pW) :	54
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242005099276
Connection rating (W) :	166
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation type :	Island



Serie | 6, Island cooker hood, 90 cm, Stainless steel DIB98JQ50B

**Stylish island chimney hoods perfectly
complement island hob installations.**

Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 445 m³/h
Intensive 867 m³/h
- Noise max. Normal Level: 54 dB*

Special features

- PerfectAir sensor
- TouchControl with lightline
- 3 power levels and 2 intensive settings
- 4 x 1.5W LED light
- Colour Temperature: 3500 K
- Dimmer function
- Efficient BLDC-technology
- Automatic after running (10 min)
- Automatic intensive revert (6mins)
- 3 removable metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Additional noise reduction insulation
- easy to clean Inner frame

Design

- Brushed steel
- Box design
- Island chimney hood
- Designed for ceiling mounted installation
- TouchControl
- Electronic control

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 445 m³/h
Intensive 867 m³/h
- Extraction rate according to EN 61591 max. 445 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 54 dB(A) re 1 pW (41 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 54 dB(A) re 1 pW (41 dB(A) re 20 µPa sound pressure)
Intensive: 69 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 54 dB (A) re 1pW
- Noise max. Normal Level: 54 dB*
- Power rating: 166 W
- Light Intensity: 423 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 31.6 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014