

Coiled Tubing Swivel Joint



FULL 360° ROTATION

SUITABLE FOR APPLICATIONS WITH JARRING

ROBUST DESIGN

Description

The DTI Coiled Tubing Swivel Joint is a fully sealed joint that provides the CT tool string with 360 degrees of rotation. The swivel enables the rotation of CT tool string at surface to allow conventional tool threaded make ups and break outs. It is also used in Coiled Tubing operations where the rotation of the lower tool string is necessary, such as when running gas lift.

The DTI Coiled Tubing uses a ball and socket design to enable the rotation of the joint without the need for bearings. This provides a robust connection that is able to withstand the effect of jarring whilst maintaining a good seal.

Features & Benefits

- Uninterrupted, sealed flow through bore.
- Internal pressure seals.
- Robust design in tension and compression.
- No bearings.

Part Number	Outside Diameter	Inside Diameter	Length	Thread
CSJ150AC08	1.500"	0.44"	7.50"	1.00 AMMT
CSJ169AC08	1.687"	0.50"	8.00"	1.00 AMMT
CSJ175AC08	1.750"	0.50"	8.00"	1.00 AMMT
CSJ212AC09	2.125"	0.63"	9.10"	1.50 AMMT
CSJ288AC23	2.875"	1.00"	11.70"	2.38 PAC

We offer optional equipment, alternative sizes, materials and thread connections.
Please contact us for more information.

