

N Type Instrument Hanger



BESPOKE DESIGN TO SUIT APPLICATION

RUN ON SLICKLINE

LARGE THROUGH BORE

Description

The DTI N Type Instrument Hangers are bespoke designed devices that enable down hole instruments or gauges to be positively landed and locked into no-go nipple profiles in the tubing string.

The tool has an internal fish neck profile and is designed to be run and pulled in slickline with a standard GS pulling tool with a suitable probe. They can also be run on slickline with a soft set type running tool. Pulling is also carried out with a standard GS Pulling Tool and probe.

The lower thread connection is typically a 15/16-10UN thread however the tools can also be supplied with 3/4" Amerada threads.

Features & Benefits

- Can be designed to suit any no-go nipple profile.
- Lock in and leave system.
- Large through bore.
- Can be run and pulled on slickline using a standard GS Pulling Tool with a probe.

Deployment and Retrieval

- GS Pulling Tool
- Running Probe
- Pulling Probe

Optional Equipment

- Shock Absorbers
- Soft Set Running Tools

Part Number	Nipple Size & Type	Outside Diameter	Fish Neck	Flow Area	Length
212HBNLACU	2.125" HBN	2.125	1.38" (2" GS)	0.8in ²	16.25"
281HBNLACU	2.813" HBN	2.790"	2.31" (2 1/2" GS)	2.3in ²	16.30"
344AFLHBCU	3.437" AF	3.495"	3.12" (3" GS)	2.4in ²	19.50"
369AFLHBCU	3.688" AF	3.740"	3.12" (3" GS)	2.4in ²	19.50"
375AFLHBCU	3.750" AF	3.850"	3.12" (3" GS)	2.4in ²	19.50"
381XBLHCCU	3.812" XN	3.800"	3.12" (3" GS)	2.4in ²	19.50"
563RNLHACU	5.625" RN	5.610"	4.00" (5" GS)	4.0in ²	20.00"

We offer optional equipment, alternative sizes, materials and thread connections.
Please contact us for more information.

