

Downhole Filters



REPLACEABLE METAL FILTER
 OPTIONAL FILTER SIZES
 STANDARD TOOLSTRING SIZES

Description

The DTI CT Downhole Filter removes particles from circulating or produced, fluid to prevent them passing through Motors or other downhole tools that are sensitive to debris.

The DTI CT Downhole Filter features an easily replaceable metal filter screen with standard filtration size of 600 microns. Other filter sizes are available on request.

The DTI Downhole Filter can be used to filter fluid for Coil tubing operations in conjunction with pumped fluids and motors, or as an intake filter for artificial lift methods such as CD ESP's and jet pumps to protect internal components from erosion or blockages.

<h3>Features & Benefits</h3>	<ul style="list-style-type: none"> ▪ Easily replaceable metal filter screen ▪ 4ft length to reduce chances of the filter plugging ▪ Different filtration sizes filter cartridges available ▪ Available with H2S and Standard Service bodies
----------------------------------	---

Part Number	OD	Filter Size	Length (MU)	Thread
FIL169AA08-1	1.688"	600 microns	48.0"	1.00 AMMT
FIL212AA09-1	2.125"	600 microns	48.0"	1.50 AMMT
FIL288AA23-1	2.125"	600 microns	48.0"	2.38 PAC

We offer optional equipment, alternative sizes, pressure ratings, materials, thread connections and filter sizes. **Please contact us for more information.**

