

# Surface Test PermaSeal External Slip Connector



15,000 PSI RATED  
 UNIQUE SLIP TEETH DESIGN ON SLIPS  
 METAL TO METAL SEALING

## Description

The DTI PermaSeal External Slip Connector provides a quick and simple means of connecting the coiled tubing string to surface equipment so that pressure testing can be carried out.

The connector is supplied with a 2" 1502" WECO Female connection to allow for direct connections to the test equipment.

The standard DTI torque through connector is 15,000 psi rated and includes the proprietary PermaSeal metal-to-metal sealing technology backed up with O-Rings to ensure a secure connection and seal.

## Features & Benefits

- Slips bite into the coiled tubing.
- Double Viton O-Ring seals with metal to metal 'PermaSeal'
- 2" 1502 Connection to make up to surface pressure equipment.
- 15,000 psi Working Pressure
- Torque Through Capability

Part Number	Coil Size	Maximum Torque	Working Pressure	End Connection
SCTMU175AA31	1.688"	0.75"	1 ¼"	2" 1502 WECO Female
SCTMU200AA31	2.125"	1.00"	1 ½"	2" 1502 WECO Female
SCTMU238AA31	2.375"	1.00"	1 ¾"	2" 1502 WECO Female

We offer optional equipment, alternative sizes, pressure ratings, materials and thread connections. **Please contact us for more information.**

