

Surface Filters



Replaceable metal filter

Optional filter sizes

15,000 PSI rated

DESCRIPTION

The Pragma Coiled Tubing Surface Filter is used to remove particles from circulating fluid, thus protecting downhole motors and other downhole tools that are sensitive to debris.

The Pragma Coiled Tubing Surface Filter features an easily replaceable metal filter screen with standard filtration size of 600 microns. Other filtration sizes are available on request.

It is recommended to use the Pragma Surface Filter to remove debris from pumped fluid and the Downhole Filter to filter debris from inside the CT.



FEATURES & BENEFITS

- Easily replaceable metal filter screen
- 4ft length to reduce chances of the filter plugging
- Different filtration sizes filter cartridges available
- Available with H2S and Standard Service bodies

Part Number	Upper Connection	Filter Size	Length	Lower Connection
52130-300	2" 1502 WECO Female	300 microns	36.0"	2" 1502 WECO Female
52130-400	2" 1502 WECO Female	400 microns	36.0"	2" 1502 WECO Female
52130-500	2" 1502 WECO Female	500 microns	36.0"	2" 1502 WECO Female
52130-600	2" 1502 WECO Female	600 microns	36.0"	2" 1502 WECO Female
52130-900	2" 1502 WECO Female	900 microns	36.0"	2" 1502 WECO Female

We offer optional equipment, alternative sizes, pressure ratings, temperature ratings, materials and thread connections.

Please contact us for more information.

