

Surface Test PermaSeal External Slip Connector



- 15,000 PSI rated
- Unique slip teeth design on slips
- Metal-to-metal sealing

DESCRIPTION

The Pragma PermaSeal External Slip Connector provides a quick and simple means of connecting the coiled tubing string to surface equipment so that pressure testing can be carried out.

The connector is supplied with a 2" 1502" WECO Female connection to allow for direct connections to the test equipment.

The standard Pragma torque through connector is 15,000 psi rated and includes the proprietary PermaSeal metal-to-metal sealing technology backed up with O-Rings to ensure a secure connection and seal.



FEATURES & BENEFITS

- Slips bite into the coiled tubing.
- Double Viton O-Ring seals with metal to metal
- 'PermaSeal'
- 2" 1502 Connection to make up to surface pressure equipment.
- 15,000 psi Working Pressure
- Torque Through Capability

Part Number	Coil Size	Maximum Torque	Working Pressure	End Connection
SCTMU175AA31	1.688"	0.75"	1 ¼"	2" 1502 WECO Female
SCTMU200AA31	2.125"	1.00"	1 ½"	2" 1502 WECO Female
SCTMU238AA31	2.375"	1.00"	1 ¾"	2" 1502 WECO Female

We offer optional equipment, alternative sizes, pressure ratings, temperature ratings, materials and thread connections.

Please contact us for more information.

