

Pragma XN Lock Mandrels



DESIGNED TO SUIT OTIS XN NIPPLE
 GENERIC DESIGN
 POSITIVE LOCKING

Description

The Pragma XN Lock Mandrel is sized by the internal seal bore of the corresponding selective X landing nipple that it locates and locks into.

XN & RN Lock Mandrels enable the positive landing and locking of subsurface flow control equipment into their matching tubing no-go nipple profiles. They can hold tubing pressure from either above or below.

The XN Locks typically have a lower pressure rating than the similar RN Locks and are typically used in lighter weight tubing applications.

Landing and setting the lock in the landing nipple is controlled by the X-Line running tool.

XN Lock Mandrels are factory tested in accordance with API 14L and are available in several materials meeting most well conditions. Individual technical data sheets are available upon request.



Features & Benefits

- Locates in the key profile of the corresponding XN landing nipple.
- Can be supplied in any material to suit application.
- Suitable for bi-directional sealing.
- A device can be screwed into the bottom thread to change it to a plug, injection valve, standing valve or hanger.

Part Number	Lock Size	Outside Diameter	Inside Diameter	Bottom Thread
150XNACL	1.500"	1.480"	0.750"	1 1/8-16 UN
188XNACL	1.875"	1.850"	1.000"	1 3/8-14 UN
231XNACL	2.313"	2.285"	1.375"	1 3/4-12 UN
275XNACL	2.750"	2.730"	1.750"	2 1/4-12 SLB
281XNACL	2.812"	2.790"	1.750"	2 1/4-12 SLB
331XNACL	3.313"	3.235"	2.120"	2 3/4-12 SLB
381XNACL	3.812"	3.800"	2.620"	3 1/16-12 SLB
412XNACL	4.125"	4.110"	2.750"	3 1/4-12 SLB
431XNACL	4.313"	4.280"	2.620"	3 1/4-12 SLB
456XNACL	4.562"	4.550"	3.120"	4-12 SLB

We offer optional equipment, alternative sizes and materials.

Please contact us for more information.

Rev 0 – May 2026