

Penetrating & Dewatering Fluid

Description

Penetrating & Dewatering Fluid is a high performance, multi-application fluid which is excellent for de-watering, penetrating, anti-corrosive and general lubricating properties. Suitable for lubricating moving parts on tools, hinges, wheels, chains, gears etc while protecting against corrosion. Has excellent penetrating properties to free stuck components due to corrosion such as valves, locks, gears etc.

Application

To use as a penetrant or de-watering agent: apply directly on to surface, repeating if required to loosen parts.
To use as a protective coating: apply onto clean, dry surfaces and allow to dry to give a protective film.
The product can last for 3-4 weeks outside and up to 6 months inside.

Environmental

Dispose of chemicals in accordance with local environmental legislation.

Handling

Normal precautions should be taken for handling chemicals. Protective clothing, eye protection and gloves should be worn. For further, details please refer to the safety data sheet.

Storage

Store in a cool, dry location between 5°C and 25°C. Protect from freezing. Avoid direct sunlight and extreme temperatures. Store the product sealed in the original container to avoid air exposure. Some products may settle during storage or transportation, ensure thorough mixing before use. See safety datasheet for list of incompatible materials and other relevant information.

Properties

Appearance: Clear blue liquid
Density @ 20°C: ~0.77
Flash point (closed cup): 20°C

Shelf Life

Storage: 24 months

Available in the following containers

