



# TAR AND GLUE REMOVER

## Description

Tar and Glue Remover is a hydrocarbon-based product specially formulated to remove bitumen, tar, asphalt and other heavy hydrocarbon deposits from surfaces including brick work, concrete, metal surfaces including tank interiors.

## Application

It is recommended to be applied undiluted to remove stubborn tar and glue deposits. Should be used in a well-ventilated area. It can be sprayed, painted or poured on the surface to be cleaned and then hosed off. High pressure washing may help remove product and deposited.

## Dilutions

Ideally, the product is used undiluted. The product may also be used in a dip tank. The product will form a loose emulsion with water and can be diluted to to 95%.

## Handling

Normal precautions should be taken for handling chemicals. Protective clothing, eye protection and gloves should be worn. For further details please refer to the safety data sheet.

## Storage

Store in a cool, dry location between 5°C and 25°C. Protect from freezing. Avoid direct sunlight and extreme temperatures. Store the product sealed in the original container to avoid air exposure. Some products may settle during storage or transportation, ensure thorough mixing before use. See safety datasheet for list of incompatible materials and other relevant information.

## Properties

Appearance: Slightly yellow, clear liquid  
Density @ 20°C: ~0.83  
Solubility: Insoluble in water but can be emulsified

## Shelf Life

Storage: 24 months

## Available in the following containers

