


Pattern Nancy Dress & Top




1





Simple
sew

NANCY TUNIC DRESS


#018




2



3




4




Simple
Sew
UNCY TUNIC DRESS
#018





5










9

1.5cm s
use 1cm s



CUTTING LINE

TAKE 1.5CM SEAM ALLOWANCE ALONG SLEEVE SIDES





10

seam allowance included
seam allowance at armhole

FOR SHORT SLEEVE VERSION

Straight grain





12

8

10

12

14

16

18

20

22



9


22





Straight grain

14




BACK BODICE

CUT TWO IN FABRIC

2

1.5cm seam allowance included
use 1cm seam allowance at armhole and neckline




TAKE 1 CM SEAM ALLOWANCE

Straight grain


*Simple
sew*

NANCY TUNIC DRESS
#018





17



18



CUT ONE FABRIC ON FOLD





20



HEMLINE FOR TOP

21

CUT



22 COLLAR

CUT FOUR IN FABRIC
TWO IN INTERFACING

6

1.5cm seam allowance included
use 1cm seam allowance
at neckline



23



FRONT BODICE

CUT ONE IN FABRIC ON FOLD

1

1.5cm seam allowance included
use 1cm seam allowance at armhole and

HEMLINE FOR TOP

24

CE
OLD

neckline



25



CUTTING LINE FOR TOP



27

8

10

12

14

16

18

20



28

20

18

16

14

12

10

8






30








33










36




Simple
sew


The Nancy Tunic Dress & Top #018

KEY

-  Wrong side
-  Right side
-  --- Stitch line
- RST = right sides of fabric together



VIEW A



VIEW B



VIEW A




VIEW B

SEAM ALLOWANCES ARE 1.5CM UNLESS OTHERWISE STATED


DRESS LAYPLAN 45"

FOLD




TOP LAYPLAN 45"

FOLD




DRESS LAYPLAN 60"

FOLD



TOP LAYPLAN 60"

FOLD




- 1 - FRONT BODICE
- 2 - BACK BODICE
- 3 - FRONT FACING
- 4 - BACK FACING
- 5 - SLEEVE
- 6 - COLLAR

GENERAL PREPARATION

It is really important to launder your fabric (according to the manufacturer's instructions) before you begin - this allows for shrinkage.

It is **ALWAYS** a really good idea to make a toile or muslin to check for fit and form before you cut into your main fabric. This way, you will achieve a really great fit and you won't waste any good fabric. Apply interfacing to the wrong side of any piece that requires it and make sure you overlock or zigzag-stitch any raw edges that will be exposed so that they don't fray in the wash. Ultimately, sewing is amazingly rewarding so just relax and enjoy the process. It can be counter-intuitive at times, and it will challenge you to think things through logically, but when you achieve what you hoped to, or near to it, you will want to come back for more and more!


1



2

Iron interfacing on to the **WRONG** side of facing pieces and RST join the front and back neck facings at the shoulders. Press seams open and zigzag or overlock bottom edge of facings.

2



Sew a line of gathering stitches along sleeve head curve and pull threads to gather sleeve until it will fit the armhole.

3



Sew darts in on the wrong side of the dress front and press upwards.

4




RST join front and back bodices together at the shoulder seams.

5




Press seams open.

6




Apply interfacing to wrong side of what you will use as the bottom pieces of the left and right collar. Sew the bottom and top piece of the left collar RST, leaving a turning through gap as shown. Trim seam to 0.5cm, snip or notch around curved edges and turn through to right sides and press.

7




With wrong sides of collar facing right sides of dress, pin in place, making sure the front collars are sitting on the centre front of neckline. Stitch in place using a 1cm seam allowance.

8




Pin neck facing in place RST with the collar. Stitch slowly using a 1cm seam allowance and take pins out as you sew.

9




Trim seams and notch around curves.

10




Turn facing through to the inside of the collar and press flat.

11




Flip facing up and on the right side of the bodice, pin your zip in place RST. Use zipper foot on your machine and sew a line of basting stitches along zip tape removing pins as you sew. Now sew a line of stitches as close to the zip teeth as you can get as far down as your foot will allow. Repeat other side.

12




Now fold your facing over the top of the zip so that the facing is RST with the back bodice. You can keep your zip footer on and stitch along the side of the zip tape through the facing and the bodice NOT THROUGH THE COLLAR. Snip the top corners.

13




Turn facing through back to the inside of the dress and press flat.

14




Turn dress RST and from the last stitch you made on the zip, sew all the way down to the beginning of the split.

15



Open out CB seam and press.

16



Now turn up skirt hem, press and stitch. Repeat for sleeve hems.

FINISH!

