



**Edu-Logger Anemometer
Logger Sensor Guide
900-260**



Edu-Logger anemometer logger sensor 900-260

The Edu-Logger anemometer sensor can be used for any science experiment or activity that utilizes wind speed such as in the fields of: Environmental Science, Weather Science, Ecology, Biology, etc.

The sensor comes pre-calibrated so you can start experimentation right out of the box using this guide.

Hundreds of possible experimental subjects that can be done with the 900-260 sensors are: weather studies, photosynthesis rates, animal behavior, insect flight, and many more.

The anemometer sensor uses the following units of measure:

- Kilometers per hour (km/hr): An SI measurement of velocity.
- Miles per hour (mph): English system measurement of velocity.

Quick start procedure:

PC or Mac Computer

Materials needed:

- 900-260 Anemometer Sensor
- 900-213 USB Module
- A USB to mini USB cable (which comes with the 900-213)

Your anemometer sensor needs to be connected to a 900-213 module. The 900-213 module then connects to a computer via a USB to mini-USB cable. Please note that you cannot plug the anemometer sensor directly into the computer.

Resident PC software and browser based application can be downloaded for free at WWW.EDULAB.COM as well as a full software user guide.

Note: Make sure not to download and install both types of software they will conflict on the computer.

Procedure:

1. Install the Edu-Logger software
2. Connect the 900-213 module to the PC or Mac
3. Connect the anemometer sensor to the 900-213 module (they directly plug together). Please note there is no calibration required for this sensor.
4. Open the Edu-Logger software.
5. Once a anemometer sensor logo appears on the left side of the screen the probe has been automatically identified and you can begin experimentation.
6. If the anemometer sensor is not automatically identified then click the “Search for sensors” icon to find the sensor.
7. Select the “On-line experiment” button; this will open a graph below.

8. Click on the “Module setup” button located on the anemometer sensor icon in the module window to change the sensor settings if need be.
9. Click on the "experiment set up button" to change the experiment settings if need be (experiment duration for example).
10. The anemometer sensor will give a live reading in the box to the left of the screen while plugged in.
11. To run an experiment and collect data click “Run experiment”.
12. To end data collection early, click “Stop experiment”.

Tablet, smart phone device

Materials needed:

- 900-260 Anemometer Sensor
- 900-268 WiFi module
- 900-215 Battery

Your anemometer sensor needs to be connected to a 900-268 module. The 900-268 module will create a closed Edu-Logger WiFi network which will stream the Edu-Logger data to a device of your choosing. Once your device is wirelessly connected to the Edu-Logger network you can run experiments and collect data through a browser of your choosing.

Procedure:

1. Connect the anemometer sensor directly to the left side 900-268 (no wires required).
2. Connect a 900-215 module to the right side of the 900-268 module.
3. Although not required, we recommend plugging the 900-215 to an outlet using a USB to mini USB charger (such as a typical cell phone

charger). The 900-268 module will run for 15-75 minutes (depending on the sensor) without being plugged in.

4. The 900-268 can be powered directly using a mini to USB cord and plugging it into your computer or a wall charger. Please note this function is only available on 900-268 units with the USB icon on the cover.
5. For further 900-268 instructions or the 900-268 quick start guide please visit: www.edulab.com
6. The 900-268 indicator lights will flash; take no action until the LED to the far left turns blue; this can take up to one minute.
7. Take your tablet or smart phone, go to the WiFi settings and select the Edu-Logger network which matches the 900-268 Module ID found on the back of the 900-268 device. (Edu-LoggerXXXX for example).
8. Give your device about 20 seconds to connect to the 900-268.
9. Once the device is connected, go to your browser and type the website **wifi201.com** into the URL bar, then wait for 30-60 seconds.
10. You will see a “Control mode” icon in the browser, click on this icon.
11. The browser will then load a new screen and begin to auto detect the sensor(s); this can take a minute. (You can stop the search when the sensor is found.)
12. If the browser does not auto detect the sensor(s), select “Search for sensors”.
13. Once the sensor is found you will see an icon on the left side of the screen for the anemometer sensor. The icon will display real time data.
14. Click on the “Module setup” button located on the anemometer sensor icon in the module window to change the anemometer probe settings if need be.

15. Click on the experiment set up button to change the experiment settings if need be (Experiment duration for example).
16. To run an experiment and collect data, select “On-Line” experiment, then select "Run".
17. If you have a newer generation 900-268 (with the USB icon on the cover) this can be used as a 900-213, meaning you can tether the probes directly to the computer using the 900-268. To engage operation in this fashion, press 3 times on the panel key. Repeating this operation will return the unit to WiFi mode.

Operation with Edu-Logger viewer

Materials needed:

- 900-260 Anemometer Sensor
- 900-272 Viewing Module
- 900-215 Battery

Procedure:

1. Connect the anemometer sensor to the left side of the viewer.
2. Connect the 900-215 module to the right side of the viewer.
3. The 900-272 will auto detect the sensor and you will see it appear on the left side of the screen.
4. Once the sensor appears it will be monitoring data in real time.
5. To run an experiment and collect data click the run button (little green person).

Off-line experiments

(Off-line experiments are for when you do not have a sensor connected directly to a computer, tablet, smartphone, or Edu-Logger viewer).

Materials needed:

- 900-260 Anemometer Sensor
- 900-215 Battery

Materials needed to configure your offline experiment:

- 900-213 Module or 900-268 module or 900-272 Module
- USB to mini USB cable (included with the 900-213 module).

Procedure:

1. Connect the anemometer sensor directly to the left side of a charged 900-215 module.
2. When ready to collect data press the “Start/Stop” button on the anemometer sensor, a red light will turn on for the duration of the experiment.
3. To change the experiment settings first connect to your chosen device (PC, Mac, tablet, smart device) and select the “Module setup” button. (For more information on how to change the experiment settings view quick start procedure section for your chosen device in this document.)
4. After the experiment has concluded (when the “Start/Stop” button is pressed again or the data collection period ends) connect the sensor to your chosen device. (full instructions in each device’s quick start procedure section)
5. Open Edu-Logger software.
6. Click the “Off-line experiment” button.
7. Click the “Load data from sensors” button.
8. Select which experimental data to upload. (5 experimental runs can be stored at one time on the 900-260 anemometer sensor)

Restoring sensor's factory default settings:

Procedure:

1. Connect the 900-213 to a PC, Mac, tablet, or smart device.
2. Connect the anemometer sensor to a 900-213 module (they directly plug together). Please note there is no calibration required for this sensor.
3. Open the Edu-Logger software.
4. Click the "Tools" icon.
5. Click the "Restore sensor's factory defaults" on the menu.
6. If prompted to clear the graph, click either the "Off-line experiment" or "On-line experiment" (whichever you are using).
7. Click "Clear experiment results".
8. Resume from step 4.

Included with sensor:

- Edu-Logger 900-260 Anemometer Sensor Guide (this document).
- Anemometer probe made from durable plastic, attached to the sensor body by a strong rubber-coated wire.

Sensor specifications		
	Miles per hour (mph)	Kilometers per hour (km/hr)
Range and operation modes	0 to 75 mph	0 to 120 km/hr
ADC resolution	15 bit	
Resolution	0.01 mph	0.01 km/hr
Max sample rate (S/sec)	100	

Sensor features:

- Fully digital data.
 - Rugged plastic ergonomic case.
 - Durable anemometer probe attached by a strong rubber-coated wire.
 - Push button switch for Start/Stop experiments in off line mode.
 - LED indicator of experiment status (blinks while collecting data).
 - Pre-calibrated sensing equipment.
- Note:** Edu-Logger products are intended for educational use.

Videos and experiment examples:

- Videos, literature and other probes can be found at www.edulab.com

Technical background:

The philosophy behind Edu-Logger's plug and play technology is based on each sensor's ability to store its own data due to an internal flash memory chip and micro-controller in each plastic Edu-Logger body. This technology allows the sensor to collect and then store the digital data in the correct scientific units ($^{\circ}\text{C}$, $^{\circ}\text{F}$, Lux, %, ppm, for example).

The sensor is pre-calibrated at the factory. The built-in software in the logger can be upgraded at any time using software.

Inside of the anemometer sensor a magnet is situated within a metal coil. The magnet is connected directly to the wind speed detector which causes the magnet to spin with the same velocity as the wind propelling it.

The shaft is installed in a bearing and has a magnet at its end. A digital sensor based on Hall Effect sensor, analog circuit and a very sophisticated digital processor is located near the rotating magnet.

The analog and digital circuits analyzes magnetic field and calculates the rotation



transfers this data to the sensor controller upon its request.

The controller converts this data into air flow velocity.

Maintenance and storage:

- Never submerge the Edu-Logger plastic body in any liquid.
- Do not allow liquid into the anemometer sensor's body.
- After use, gently wipe away any foreign material from the anemometer sensor.
- Store in a box at room temperature out of direct sunlight.

Warranty:

We promise to deliver our sensor free of defects in materials and workmanship for a period of 3 years from the date of purchase. Our warranty does not cover damage of the product caused by improper use, abuse, or incorrect storage. Sensors with a shelf life such as ion selective probes have a warranty of 1 year. Should you need to act upon the warranty please contact your distributor. Your sensor will be repaired or replaced.

Thank you for using Edu-Logger!

W: www.edulab.com

E: info@edulab.com

V10202013