



Application

The Aries LED is a domed bollard with a built in light source. The Aries LED is designed for outdoor areas with an IP65/IK10 rating and easily accessible ballast tray for maintenance.

Ideal for:

- Car Parks
- Pavements/Walkways
- External Vehicle Areas

Body

Extruded aluminium housing with flush mounting base, vandal-resistant screws and a black powder-coat finish over a chromate conversion coating. IP65/IK10 rated.

Sizes (nominal)

Height: 1073 mm
Diameter: 178 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

- Add /EMG to codes for Emergency Mode
- Add /BLK to codes for Black Housing
- Add /SS to codes for Stainless Steel Housing

Attachments

- Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 92lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee



Catalogue Codes

Wattage	Diameter	Height	Catalogue Code
15 W	178 mm	1073 mm	SL/LED/2000/ARI

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.