



Application

The Bedhead LED gives a unique look whilst still giving an IP54 rating, maintaining the environment required in a Hospital.

Body

Formed from 1mm Zintec steel or dia cast aluminium finished in fine textured white, IP rated as standard. A high output/low glare opal diffuser is used in both direct and indirect light.

Sizes (nominal)

- 600 mm
- 900 mm

Other sizes available as specials to order.

Control Gear

Standard LED

Options Available

- Emergency Mode
- Direct & Indirect Light
- Direct Light Only
- Indirect Light Only

Lamps

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius



Catalogue Codes

| Length | Width | Depth | Cat No. |
|--------|--------|-------|------------------------|
| 600 mm | 220 mm | 98 mm | SL/LED/6/2560/BH/IP/LO |
| 600 mm | 220 mm | 98 mm | SL/LED/6/2740/BH/IP/MO |
| 600 mm | 220 mm | 98 mm | SL/LED/6/2940/BH/IP/HO |
| 900 mm | 220 mm | 98 mm | SL/LED/9/3600/BH/IP/LO |
| 900 mm | 220 mm | 98 mm | SL/LED/9/4100/BH/IP/MO |
| 900 mm | 220 mm | 98 mm | SL/LED/9/4900/BH/IP/HO |

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.