



Application

Bliss LED is a high specification IP20, decorative wall mounted luminaire. A unique diffuser design is utilised to maximise LED light output with no LEDs visible.

Ideal for:

- Staircases
- Corridors
- Toilets
- Social Areas

Body

The body is formed from 1 mm Zintec steel and coloured to any RAL colour. A high output/low glare opal diffuser produced from poly-carbonate.

Sizes (nominal)

- 620 mm

Control Gear

Standard LED

Options Available

- Add /DALI to Cat No. for DALI Dimming
- Add /EMG to Cat No. for Emergency Mode
- Add /PIR to Cat No. for Inbuilt PIR Sensor

Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 136lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Length	Width	Depth	Milliamp	Catalogue Code
23.6 W	620 mm	165 mm	75 mm	300 mA	SL/LED/3570/BLS/WL/300mA/HO
25.8 W	620 mm	165 mm	75 mm	325 mA	SL/LED/3820/BLS/WL/325mA/HO
27.5 W	620 mm	165 mm	75 mm	350 mA	SL/LED/4140/BLS/WL/350mA/HO
29.5 W	620 mm	165 mm	75 mm	375 mA	SL/LED/4410/BLS/WL/375mA/HO

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533.
A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.