



Application

A new concept using IP44 LED Technology to produce direct/indirect (70% down / 30% upward) illuminance to create an environment in line with CIBSE LG7. This fitting can be wire suspended/standalone.

Ideal for:

- Offices
- Reception Areas
- Libraries
- Schools

Body

Formed from 1 mm steel powder coated white or any RAL Colour required. The downward light aspect is controlled via an high output diffuser giving a very high L.O.R and the backward light through clear polycarbonate.

Sizes (nominal)

- 1195 x 295 mm

Other sizes can be manufactured, as specials to order.

Control Gear

Standard LED

Options Available

- Dimming: DALI/DSI
- Integral, Self Test or EM-PRO Emergency
- Wire Suspension
- Rod Suspension

Attachments

When linked with the Digital Control Systems, the luminaire can offer PIR Presence detection automatic switch on / off.

Controlled Daylight Sensing/ dimming to create a constant working illuminance.

Lamps

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- Up to 115lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Length	Width	Depth	Cat No.
26 W	1195 mm	295 mm	18 mm/42 mm	SL/LED/12.3/3000/CLM/MP/WS
35 W	1195 mm	295 mm	18 mm/42 mm	SL/LED/12.3/4000/CLM/MP/WS
44 W	1195 mm	295 mm	18 mm/42 mm	SL/LED/12.3/5000/CLM/MP/WS
55 W	1195 mm	295 mm	18 mm/42 mm	SL/LED/12.3/6000/CLM/MP/WS

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.