



Application

A Stylish and decorative approach using LED technology to modern day Modular lighting, combining direct and indirect illuminance to create a comfortable and bright ambiance.

Ideal for Reception areas, Board Rooms and General Office Lighting where luminaires can help towards meeting CIBSE LG7.

Body

Formed from one piece, 1mm bright steel, Finished in high gloss electrostatic white powder coating.

Sizes (nominal)

Available in
600 x 600, 500 x 500, 1200 x 600, 1200 x 300, 1500 x 300

Control Gear

Standard
High Frequency Driver
Options Available
High Frequency Dimming DSI or DALI
Emergency Mode
Addressable Emergency

Attachments

An Inbuilt Sensor unit gives this Luminaire an intelligence of its own. When linked with the Digital Control Systems, the luminaire can offer PIR Presence Detection automatic switch on / off. Control Daylight Sensing / Dimming to create a constant working illuminance. The luminaire can also be incorporated into a Bus-wire system eliminating the "loan worker" syndrome by illuminating designated pathways. In-fa Red remote control of one or any Bank of luminaires can be achieved by a remote hand held unit.

Main Attributes

- . Up to 136lm/watt
- . 50,000 Hour Life
- . High Colour Rendering
- . Self Cooling
- . 5 Year Guarantee

Lamps

All Luminaries are supplied with colour 840, 4000k LED's as standard.

Options are available from 3000k to 5000k.

All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius



Catalogue Codes

| Modular Size | Lamp Rating | Length | Width | Depth | Catalogue Codes |
|--------------|-------------|--------|-------|-------|-----------------------------|
| 600 x 300 | 2 x 9.8 w | 595mm | 295mm | 113mm | SL/LED/6.3/2560/CAN/W2/LO |
| 600 x 600 | 4 x 9.8 w | 595mm | 595mm | 113mm | SL/LED/6.6/5120/CAN/W2/LO |
| 1200 x 300 | 4 x 9.8 w | 1195mm | 295mm | 113mm | SL/LED/12.3/5120/CAN/W2/LO |
| 1200 x 600 | 8 x 9.8 w | 1195mm | 595mm | 113mm | SL/LED/12.6/10240/CAN/W2/LO |
| 1500 x 300 | 5 x 9.8 w | 1495mm | 295mm | 113mm | SL/LED/15.3/6400/CAN/W2/LO |
| 600 x 300 | 2 x 11.6 w | 595mm | 295mm | 113mm | SL/LED/6.3/2940/CAN/W2/HO |
| 600 x 600 | 4 x 11.6 w | 595mm | 595mm | 113mm | SL/LED/6.6/5880/CAN/W2/HO |
| 1200 x 300 | 4 x 11.6 w | 1195mm | 295mm | 113mm | SL/LED/12.3/5880/CAN/W2/HO |
| 1200 x 600 | 8 x 11.6 w | 1195mm | 595mm | 113mm | SL/LED/12.6/11760/CAN/W2/HO |
| 1500 x 300 | 5 x 11.6 w | 1495mm | 295mm | 113mm | SL/LED/15.3/7350/CAN/W2/HO |

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.