



Application

A stylish and decorative approach using LED technology to modern day Modular lighting, combining direct and indirect illuminance to create a comfortable and bright ambiance.

Ideal for:

- Reception areas
- Board Rooms
- General Office Lighting where luminaires can help towards meeting CIBSE LG7.

Body

Formed from 1mm piece bright steel, finished in white semi-matt. High output Micro-prism diffuser ensures a High L.O.R is maintained. Air handling facilities are available on request.

Sizes

(nominal) Length:
600/1200 mm Width:
300/600 mm Depth:
100 mm

Control Gear

- Standard LED
- DALI Dimmable LED
- DSI Dimmable LED

Options Available

Add /EMG to codes for Emergency Mode
Add /EMG/ST to codes for Self Test Emergency
Add /EMG/AD to codes for Addressable Emergency

Attachments

Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 136lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Lumens	Length	Width	Depth	Catalogue Code
19.9 W	2829 lm	595 mm	595 mm	100 mm	SL/LED/3290/CAN/WAVE
24.4 W	3517 lm	595 mm	595 mm	100 mm	SL/LED/4090/CAN/WAVE
29.0 W	4197 lm	595 mm	595 mm	100 mm	SL/LED/4880/CAN/WAVE
34.0 W	4833 lm	595 mm	595 mm	100 mm	SL/LED/5620/CAN/WAVE
39.0 W	5435 lm	595 mm	595 mm	100 mm	SL/LED/6320/CAN/WAVE
44.0 W	6020 lm	595 mm	595 mm	100 mm	SL/LED/7000/CAN/WAVE
49.2 W	6553 lm	595 mm	595 mm	100 mm	SL/LED/7620/CAN/WAVE

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.