



Application

Designed for compatibility with today's commercial interiors. This wall mounted version gives a combination of upward and downward light to produce an efficient optical system.

Body

Precisely rolled steel perforated lower section with injected moulded endcaps.

Sizes (nominal)

- 300mm
- 600mm
- 900mm

Other sizes can be manufactured, as specials to order.

Control Gear

Standard LED

Options Available

- High Frequency Digital Dimming
- Emergency Mode
- Opal or Clear Polycarbonate Diffuser
- Inbuilt PIR

Lighting Control

All luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Catalogue Codes

Length	Width	Depth	Catalogue Code
300 mm	195 mm	135 mm	SL/LED/3/980/CAS/UP/LO
300 mm	195 mm	135 mm	SL/LED/3/1600/CAS/UP/HO
600 mm	195 mm	135 mm	SL/LED/6/1760/CAS/UP/LO
600 mm	195 mm	135 mm	SL/LED/6/3300/CAS/UP/HO
1200 mm	195 mm	135 mm	SL/LED/12/3520/CAS/UP/LO
1200 mm	195 mm	135 mm	SL/LED/12/6600/CAS/UP/HO

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.