



Application

The Cloud LED is a unique product large in size that creates an impressive lighting appearance, containing multiple LED's and wattage's.

Ideal for:

- PublicAreas
- EntranceFoyer
- Open OfficeEnvironments

Body

Manufactured from 1mm spun steel housing. Powder coated silver as standard.
UV Stabilized High output diffuser to comply with modern day demands onefficiency.

Sizes (nominal)

- 600 mm
- 900 mm
- 1200 mm

Control Gear

Standard LED

Options Available

- High Frequency DigitalDimming
- EmergencyMode
- WireSuspensions
- RodSuspensions
- PolychromaticDiffuser
- Any RALColour

Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to136lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- 5 YearGuarantee



Catalogue Codes

Lamp Type	Diameter	Depth	Catalogue Code
26.5 W	600 mm	110 mm	SL/LED/3360/6/CLO/200
31.6 W	600 mm	110 mm	SL/LED/4200/6/CLO/250
37.2 W	600 mm	110 mm	SL/LED/4920/6/CLO/300
43.2 W	600 mm	110 mm	SL/LED/5640/6/CLO/350
47.3 W	1200 mm	110mm	SL/LED/6624/12/CLO/200
57.6 W	1200 mm	110 mm	SL/LED/8280/12/CLO/250
68.8 W	1200 mm	110 mm	SL/LED/9720/12/CLO/300
80.4 W	1200 mm	110 mm	SL/LED/11080/12/CLO/350

Additional lumen outputs are available and codes may vary from those stated. Lumen outputs for the 900 mm version are identical to the 1200 mm version. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.