



Application

The light-weight appearance of the Cocoon makes it the perfect fitting for high ceiling rooms such as receptions and lobbies where suspended fittings are required.

Body

Formed from steel the body can be powder coated to any RAL colour. The downward light aspect is controlled with a high output diffuser.

Sizes (nominal)

Depth: 600/900/1300 mm

Diameter: 110 mm

Other depths can be manufactured as specials to order.

Control Gear

- StandardLED
- DALI DimmingLED
- DSI DimmingLED

Options Available

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /DSI to codes for DSI Dimming

Attachments

- Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- 120lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- CRI>80
- 5 YearGuarantee

Catalogue Codes

Wattage	Lumens	Diameter	Depth	Catalogue Code
6.2 W	726 lm	127 mm	900 mm	SL/LED/820/CCN
7.9 W	965 lm	127 mm	900 mm	SL/LED/1090/CCN
9.7 W	1204 lm	127 mm	900 mm	SL/LED/1360/CCN
11.8 W	1372 lm	127 mm	900 mm	SL/LED/1550/CCN
13.6 W	1602 lm	127 mm	900 mm	SL/LED/1810/CCN

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.