



Application

Comet LED is a decorative surface mounted fitting which is available in two diameters, utilising LED technology.

Ideal for:

- Offices
- Corridors
- Schools

Body

Aluminium base in brushed or white finish, either 330mm or 400mm diameter. Diffuser made from PMMA fire retardant opal polycarbonate.

Sizes

(nominal) Diameter:
330/400 mm Depth:
98/113 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED
- WI-FI

Options Available

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /DSI to codes for DSI Dimming
- Add /WI-FI to codes for Wireless Control

Attachments

- Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- . Up to 96lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Lamp Type	Diameter	Depth	Catalogue Code
10w	330 mm	98 mm	SL/LED/1200/COM
11w	330 mm	98 mm	SL/LED/1320/COM
14w	330 mm	98 mm	SL/LED/1680/COM
19w	330 mm	98 mm	SL/LED/2200/COM

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.