



#### Application

Designed for compatibility with today's commercial interiors the Cornice LED offers an IP65, anti-ligature and IK10 rating. This corner mounted fitting gives a downward light to produce an efficient optical system.

Ideal for:

- Prisons/Cells
- Industrial Maintenance Areas
- Pit/Underground Areas

#### Body

Formed from 1.5 mm Steel, powder coated in Silver, White or any RAL Colour required. A 5 mm poly-carbonate diffuser is combined with anti tamper screws giving the fitting its IP65/anti-ligature rating. IK10 rated.

#### Sizes (nominal)

Length: 1200 mm/1700 mm

Width: 100 mm

Depth: 70 mm

Other sizes can be manufactured, as specials to order.

#### Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

#### Options Available

Add /EMG to codes for Emergency Mode  
Add /AD to codes for Addressable Emergency

#### Attachments

Add /PIR to codes for Inbuilt PIR

#### Lamps

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k.

All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

#### Main Attributes

- Up to 136lm/watt
- 100,000 Hour Life
- High Colour Rendering
- Self Cooling
- 8 Year Guarantee

## Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
14.9 W	1210 mm	100 mm	70 mm	SL/LED/12/2760/COR
15.7 W	1210 mm	100 mm	70 mm	SL/LED/12/3290/COR
18.6 W	1210 mm	100 mm	70 mm	SL/LED/12/3680/COR
20.7 W	1210 mm	100 mm	70 mm	SL/LED/12/4720/COR
27.8 W	1770 mm	100 mm	70 mm	SL/LED/17/4140/COR
33.5 W	1770 mm	100 mm	70 mm	SL/LED/17/4890/COR
39.2 W	1770 mm	100 mm	70 mm	SL/LED/17/5520/COR
43.5 W	1770 mm	100 mm	70 mm	SL/LED/17/7080/COR
53.6 W	1770 mm	100 mm	70 mm	SL/LED/17/8280/COR
65.0 W	1770 mm	100 mm	70 mm	SL/LED/17/9720/COR
76.4 W	1770 mm	100 mm	70 mm	SL/LED/17/11040/COR
85.1 W	1770 mm	100 mm	70 mm	SL/LED/17/14160/COR

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.