



#### Application

Eclipse is a High Specification IP44 decorative luminaire. A unique diffuser design is utilised to maximise LED light output with no LEDs visible.

Ideal for:

- Staircases
- Corridors
- Toilets
- Social Areas

#### Body

Formed from UV stabilised poly-carbonate for both body and diffuser. The decorative bezel is available in a range of options.

#### Sizes (nominal)

Diameter: 525 mm  
Depth: 122 mm

#### Control Gear

- Standard LED
- DALI Dimmable LED
- DSI Dimmable LED

#### Options Available

Add /EMG to codes for Emergency  
Add /EMG/ST to codes for Self-Test Emergency  
Add /EMG/AD to codes for Addressable Emergency  
Add /DALI to codes for DALI Dimming  
Add /DSI to codes for DSI Dimming  
Add /WS to codes for Suspension Kit  
Add /IP65 to codes for IP65 Gasket

#### Attachments

Add /PIR to codes for Inbuilt PIR

#### LED Boards

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

#### Main Attributes

- Up to 130lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee



#### Catalogue Codes

Wattage	Lumens	Diameter	Depth	Catalogue Code
20.0 W	2572 lm	432 mm	122 mm	SL/LED/3080/EC
29.7 W	3674 lm	432 mm	122 mm	SL/LED/4400/EC

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.