



Application

A small unobtrusive emergency down light ideal for most office and commercial areas. Producing effective emergency lighting.

Body

Manufactured from thermally optimised die-cast aluminium.

Control Gear

- Standard LED Emergency
- Self-Test LED Emergency
- Addressable EM-Pro LED Emergency

Options Available

Add /ST to codes for Self Test Emergency
Add /EMPRO to codes for Addressable Emergency

Attachments

Add /110 to codes for 110 Degree Beam
Add /60 to codes for 60 Degree Beam

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- 60 Degree or 120 Degree Beam
- 100% Light Output
- 50,000 Hour Life
- 5 Year Guarantee

Catalogue Codes

Wattage	Lumens	Cut-Out	Diameter	Depth	Catalogue Code
3 W	208 lm	110 mm	120 mm	67 mm	SL/LED/3W/OA/S/NM3
3 W	208 lm	110 mm	120 mm	67 mm	SL/LED/3W/ER/S/NM3

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.