



### Application

Where small decorative state of the art downlighters are required our Eros MKII LED offers exceptional performance and an IP40 rating as standard.

Ideal for:

- Receptions
- Lobbys
- Double Height Areas

### Body

It is fitted with a transparent glass diffuser, which is fixed with a gold or black twist and lock bezel as standard. The fittings aluminium housing is available in black or white. IP40 rated.

### Sizes (nominal)

Diameter: 60 mm  
Depth: 400 mm  
Suspension: 1950 mm (max)

### Control Gear

- Standard LED
- DALI Dimmable LED
- DSI Dimmable LED

### Options Available



Add /EMG to codes for Emergency  
Add /EMG/ST to codes for Self-Test Emergency  
Add /EMG/AD to codes for Addressable Emergency  
Add /DALI to codes for DALI Dimming  
Add /DSI to codes for DSI Dimming

### LED Boards

All Luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

### Main Attributes

- 100-130lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee



### Catalogue Codes

Wattage	Diameter	Depth	Catalogue Code
3.5 W	60 mm	350 mm	SL/LED/3/298/EROS/MKII/SUS
3.5 W	60 mm	500 mm	SL/LED/5/298/EROS/MKII/SUS
8.5 W	60 mm	250 mm	SL/LED/2/1117/EROS/MKII/SUS
8.5 W	60 mm	400 mm	SL/LED/4/1117/EROS/MKII/SUS

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.