



Application

Where small decorative state of the art downlighters are required our Eros Blacklight LED offers exceptional performance and an IP44 rating as standard where a decorative appearance is required. With high visual comfort from our high contrast Black glare controloptics.

Idealfor:

- Receptions
- Circulationarea
- Toilets

Body

Die-cast aluminium body and a moulded poly-carbonate reflector, with a high specification low glare coating.

Sizes (nominal)

Length: 255 mm
Width: 85 mm
Depth: 105 mm
Cutout: 243x81 mm

Control Gear

- StandardLED
- DALI DimmingLED
- DSI DimmingLED

Options Available

Add /EMG to codes for Emergency Mode
Add /PB to codes for Plaster-in Bezel

Attachments

Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to105lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- 5 YearGuarantee



Catalogue Codes

Wattage	Cut-out Length	Cut-out Width	Length	Width	Depth	Cat No.
17.3 W	243 mm	81 mm	255 mm	85 mm	105 mm	SL/LED/1950/EROS/SQ/BKR/T
11.4 W	243 mm	81 mm	255 mm	85 mm	105 mm	SL/LED/3600/EROS/SQ/BKR/T

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533.

A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.