



Application

Where small decorative state of the art downlighters are required our Eros Blacklight LED offers exceptional performance and an IP44 rating as standard. Ideal for offices, receptions, circulation area, toilets etc. where a decorative appearance is required.

Body

Die-cast aluminium body and a moulded polycarbonate reflector.

Sizes

(nominal) Available

in (mm): Cutout:

81mm

Length x Width: 85 x 85mm

Depth: 95mm

Control Gear

Standard

-Touch & Dali

Options Available

-DSI

-0-10V Analogue

Options Available

-Different colour temperatures.

-Available in a square or round design.

-Plaster-in bezel.

Attachments

Different Lense Options

Lighting Control

Using the Samsung LEDs we achieve outstanding efficiency values, up to 105 lm/w and a rated life of 50000 hours. Our optimized slim thermal management system ensures quality is maintained.

Catalogue Codes

Wattage	Cut-out Size	Length	Width	Depth	Cat No.
5.75 W	81 mm	85 mm	85 mm	95 mm	SL/LED/650/EROS/SQ/BKR/WW
11.4 W	81 mm	85 mm	85 mm	95 mm	SL/LED/1200/EROS/SQ/BKR/WW

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.