



Application

Where small decorative state of the art downlighters are required our Eros LED offers exceptional performance. Ideal for Offices, Receptions, Circulation Area, Toilets etc.

where a decorative appearance or high end display lighting is required.

Body

Formed from brushed aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

Control Gear

Standard

-Touch & Dali

Options Available

-DSI

-0-10V analogue

-Emergency mode 60° or 110° beam for corridors

Options Available

-Different Colour Temperatures

-24° or 54° Beam Angle

-Available in a square or round design.

Attachments

Different Lense Options

Lighting Control

Using the Phillips LED's we achieve outstanding efficiency values, up to 85 lm/w and a rated life of 50000 hours. Our optimized slim thermal management system ensures quality is maintained.

Code Options

Add /WH for White

Add /BSS for Brushed Stainless Steel



Catalogue Codes

Wattage	Cut Out Size	Bezel Size	Depth	Cat No
7.5 W	80 mm	92 mm	80 mm	SL/LED/560/EROS/ADJ
12.6 W	80 mm	92 mm	80 mm	SL/LED/1098/EROS/ADJ

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.