



Application

Where small decorative state of the art downlighters are required our Eros MKII LED offers exceptional performance and an IP54/FR90 rating as standard.

Ideal for:

- Offices
- Receptions
- CirculationAreas
- Toilets
- Apartments

Body

It is fitted with a multi-faceted reflector and a white twist and lock bezel as standard, with matt black and brushed bezel options. Tested in the UK, it has been given a fire rating of FR90 and is IP54 compliant.

Sizes (nominal)

Diameter: 82 mm
Depth: 58 mm
Cutout: 70 mm

Control Gear

- StandardLED
- DALI DimmableLED
- DSI DimmableLED

Options Available

Add /EMG to the Codes for Emergency Lighting
Add /SS for Brushed Stainless Steel
Add /WH for White
Add /BK for Black

Attachments

Add /PIR to the Codes for PIR Daylight Control

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- Up to 120lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- 5 YearGuarantee

Catalogue Codes

Wattage	Lumens	Cut-Out	Diameter	Depth	Catalogue Code
4.4 W	455 lm	70 mm	82 mm	58 mm	SL/LED/540/EROS/MKII
6.2 W	690 lm	70 mm	82 mm	58 mm	SL/LED/820/EROS/MKII
7.9 W	918 lm	70 mm	82 mm	58 mm	SL/LED/1090/EROS/MKII
9.7 W	1145 lm	70 mm	82 mm	58 mm	SL/LED/1360/EROS/MKII
11.8 W	1305 lm	70 mm	82 mm	58 mm	SL/LED/1550/EROS/MKII

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.