



Application

Where small decorative state of the art downlighters are required our Eros MKII LED Adjustable offer exceptional performance and an IP54 rating.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets
- Apartments

Where a decorative appearance or high end display lighting is required.

Body

Formed from brushed aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

Sizes (nominal)

- 95 x 55 mm

Control Gear

Standard LED

Options Available

- Different Lense Options
- Different colour temperatures
- 24°, 36° or 80° Beam Angle
- Available in a square or round design.
- Add /SS for Brushed Stainless Steel
- Add /WH for White
- Add /CH for Chrome
- Add /BK for Black

Lamps

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 125lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee



Catalogue Codes

Wattage	Lumens	Cut-Out	Diameter	Depth	Catalogue Code
4.4 W	455 lm	70 mm	82 mm	58 mm	SL/LED/540/EROS/MKII/ADJ
6.2 W	690 lm	70 mm	82 mm	58 mm	SL/LED/820/EROS/MKII/ADJ
7.9 W	918 lm	70 mm	82 mm	58 mm	SL/LED/1090/EROS/MKII/ADJ
9.7 W	1145 lm	70 mm	82 mm	58 mm	SL/LED/1360/EROS/MKII/ADJ
11.8 W	1305 lm	70 mm	82 mm	58 mm	SL/LED/1550/EROS/MKII/ADJ

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.