



Application

Where small decorative state of the art downlighters are required our Eros MKII LED offers exceptional performance and an IP65 rating as standard.

Ideal for:

- Offices
- Receptions
- CirculationAreas
- Toilets
- Apartments

Body

It is fitted with a multi-faceted reflector and a white twist and lock bezel as standard, with matt black and brushed bezel options. Tested in the UK, it has been given a rating of IP65 compliant.

Sizes (nominal)

Diameter: 85 mm
Depth: 60 mm
Cutout: 73 mm

Control Gear

- StandardLED
- DALI DimmableLED
- DSI DimmableLED

Options Available

Add /EMG to codes for Emergency Mode

Attachments

Add /PIR to codes for PIR Daylight Control
Add /WH to codes for White Bezel
Add /BLK to codes for Black Bezel
Add /BSB to codes for Brushed Steel Bezel

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 120lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- 5 YearGuarantee

Catalogue Codes

Wattage	Cut-Out Size	Bezel Size	Depth	Catalogue Code
8.6 W	73 mm	85 mm	60 mm	SL/LED/600/EROS/MKII/IP65/FR

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.