



Application

The Aries LED is a domed bollard with a built in light source. The Aries LED is designed for outdoor areas with an IP66/IK10 rating and easily accessible ballast tray for maintenance.

Ideal for:

- Car Parks
- Pavements/Walkways
- External Vehicle Areas

Body

Extruded aluminium housing with flush mounting base, vandal-resistant screws, flat top and a black powder-coat finish over a chromate conversion coating. IP65/IK10 rated.

Sizes (nominal)

Height: 882 mm
Diameter: 234 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

- Add /EMG to codes for Emergency Mode
- Add /BLK to codes for Black Housing
- Add /SS to codes for Stainless Steel Housing

Attachments

- Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- Up to 115lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Height	Diameter	Catalogue Code
10.0 W	882 mm	234 mm	SL/LED/1150/GEO
20.0 W	882 mm	234 mm	SL/LED/2300/GEO

Control Gear Coding

SGL/HF - Denotes High Frequency
SGL/HFD - Denotes High Frequency DSI Dimming
SGL/HF/DALI - Denotes High Frequency DALI Dimming
EMG - Denotes Standard Integral Emergency
EMG/ST - Denotes Visual Self Test
EMG/AD - Denotes Addressable Emergency

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533.
A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.

Conditions

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification.