



Application

Where state of the art downlighters are required our Hayley LED offers exceptional performance where a decorative appearance is required. IP54 as standard.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets

Body

Formed from Die-Cast aluminium complete with a high performance heatsink to ensure life and lumen package. IP54 and IK10 rated.

Sizes

(nominal) Diameter: 195mm
Depth: 115mm
Cutout: 176mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED
- DMX Colour Changing LED

Options Available

Add /EMG to codes for Emergency
Add /EMG/ST to codes for Self-Test Emergency
Add /EMG/AD to codes for Addressable Emergency
Add /DALI to codes for DALI Dimming
Add /DSI to codes for DSI Dimming
Add /DMX to codes for Colour Changing

Attachments

Add /PIR to codes for PIR Control
Add /WH to codes for White Bezel
Add /CH to codes for Chrome Bezel
Add /BA to codes for Brushed Aluminium Bezel
Add /SM to codes for Saturn Matt Reflector
Add /DO to codes for Domed Opal Diffuser
- Trimless Plastered-In (No Bezel)

LED Boards

All Luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 140lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee



Catalogue Codes

Wattage	Lumens	Cut-Out	Diameter	Depth	Catalogue Code
9.1 W	1175 lm	176 mm	195 mm	115 mm	SL/LED/1250/HAY
12.6 W	1478 lm	176 mm	195 mm	115 mm	SL/LED/1760/HAY
16.2 W	2106 lm	176 mm	195 mm	115 mm	SL/LED/2240/HAY
19.8 W	2735 lm	176 mm	195 mm	115 mm	SL/LED/2910/HAY
23.5 W	3187 lm	176 mm	195 mm	115 mm	SL/LED/3390/HAY
27.1 W	3600 lm	176 mm	195 mm	115 mm	SL/LED/3830/HAY
44.4 W	5405 lm	176 mm	195 mm	115 mm	SL/LED/5750/HAY

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.