



Application

Where state of the art downlighters are required our Hayley LED FGR offers exceptional performance.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets

Body

Formed from Die-Cast aluminium complete with a high performance heatsink to ensure life and lumen package. An etched glass is used with spaces to give a decorative floating effect.

Sizes (nominal)

Diameter: 195 mm

Depth: 145 mm

Cut out: 175 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

Add /EMG to codes for Emergency Mode

Attachments

Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 120lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Cut Out Size	Bezel Size	Depth	Cat No.
8.2 W	176 mm	195 mm	145 mm	SL/LED/1150/HAY/FGR/IP44
15.6 W	176 mm	195 mm	145 mm	SL/LED/2120/HAY/FGR/IP44
24.1 W	176 mm	195 mm	145 mm	SL/LED/3120/HAY/FGR/IP44

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533.
A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.