



Application

Where state of the art downlighters are required our Hayley LED offers exceptional performance where a decorative appearance is required. IP54 as standard. Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets

Body

Formed from Die-Cast aluminium complete with a high performance heatsink to ensure life and lumen package.

Sizes

(nominal) Diameter: 195mm
Depth: 115mm
Cutout: 176mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED
- DMX Colour Changing LED

Options Available

Add /EMG to codes for Emergency
Add /EMG/ST to codes for Self-Test Emergency
Add /EMG/AD to codes for Addressable Emergency
Add /DALI to codes for DALI Dimming
Add /DSI to codes for DSI Dimming
Add /DMX to codes for Colour Changing

Attachments

Add /PIR to codes for PIR Control
Add /WH to codes for White Bezel
Add /CH to codes for Chrome Bezel
Add /BA to codes for Brushed Aluminium Bezel
Add /SM to codes for Saturn Matt Reflector
Add /DO to codes for Domed Opal Diffuser

LED Boards

All Luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- 120-150lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee



Catalogue Codes

Wattage	Cut Out Size	Bezel Size	Depth	Catalogue Code
7.8 W	176 mm	195 mm	115 mm	SL/LED/1156/HAY/GS
11.3 W	176 mm	195 mm	115 mm	SL/LED/1632/HAY/GS
14.9 W	176 mm	195 mm	115 mm	SL/LED/2040/HAY/GS
18.5 W	176 mm	195 mm	115 mm	SL/LED/2703/HAY/GS
22.2 W	176 mm	195 mm	115 mm	SL/LED/3153/HAY/GS

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.