



### Application

Where state of the art downlighters are required our HayleyLEDsurfaceoffersexceptionalperformance where a decorative appearance is required. IP54 as standard.

Ideal for:

- Offices
- Receptions
- CirculationAreas
- Toilets

### Body

Formed from 1mm Spun steel and finished in white as standard. Complete with a high performance heat sinkto ensure life and lumenpackage.

### Sizes (nominal)

Diameter: 202 mm  
Depth: 240 mm

### Control Gear

- StandardLED
- DALI DimmingLED
- DSI DimmingLED
- DMX Colour ChangingLED

### Options Available

Add /EMG to codes for Emergency  
Add /EMG/ST to codes for Self-Test Emergency  
Add /EMG/AD to codes for Addressable Emergency  
Add /DALI to codes for DALI Dimming  
Add /DSI to codes for DSI Dimming  
Add /DMX to codes for Colour Changing

### Attachments

Add /PIR to codes for PIR Control  
Add /WH to codes for White Bezel  
Add /CH to codes for Chrome Bezel  
Add /BA to codes for Brushed AluminiumBezel  
Add /SM to codes for Saturn Matt Reflector  
Add /DO to codes for Domed Opal Diffuser  
Add /SUS to codes forSuspension

### LED Boards

Using the Tridonic Generation 3 LED we achieve outstanding efficiency values, up to 120 lm/w and a rated life of 50000 hours. Our optimized thermal management system ensures quality is maintained.

### Main Attributes

- 120-150lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- CRI>80
- 5 YearGuarantee



### Catalogue Codes

Wattage	Diameter	Depth	Catalogue Code
7.8 W	202 mm	240 mm	SL/LED/1156/HAY/SUR
11.3 W	202 mm	240 mm	SL/LED/1632/HAY/SUR
14.9 W	202 mm	240 mm	SL/LED/2040/HAY/SUR
18.5 W	202 mm	240 mm	SL/LED/2703/HAY/SUR
22.2 W	202 mm	240 mm	SL/LED/3153/HAY/SUR

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.