



Application

Where state of the art downlighters are required our Hayley SlimlineLED offer exceptional performance where a decorative appearance is required. IP54 as standard.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets

Body

Formed from Die-Cast aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

Sizes (nominal)

95 x 110 mm
162 x 180 mm
224 x 240 mm

Control Gear

Standard LED

Options Available

- Add /DALI for DALI Dimming
- Add /EMG for Emergency Mode
- Add /PIR for Inbuilt PIR
- Add /IP65 for IP65 Bezel
- Add /WH for White Bezel
- Add /CH for Chrome Bezel
- Add /BA for Brushed Aluminium Bezel

Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 85lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Cut Out Size	Bezel Size	Depth	Cat No.
8.0 W	95 mm	110 mm	24 mm	SGL/LED/710/HAY/SLIM
13.0 W	162 mm	180 mm	24 mm	SGL/LED/1280/HAY/SLIM
15.0 W	224 mm	235 mm	24 mm	SGL/LED/1580/HAY/SLIM
18.0 W	224 mm	235 mm	24 mm	SGL/LED/1800/HAY/SLIM
20.0 W	224 mm	235 mm	24 mm	SGL/LED/2000/HAY/SLIM

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.