



### Application

Where state of the art downlighters are required our Hayley Square LED UGR19 offers exceptional performance where a decorative appearance is required. IP54 as standard meeting the requirement of UGR>19.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets

### Body

Formed from Die-Cast aluminium complete with a high performance heatsink to ensure life and lumen package.

### Sizes (nominal) Length:

110/190/228mm Width:

110/190/228 mm Depth:

139/43.5 mm Cutout:

95/170/210mm

### Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

### Options Available

- Add /EMG to codes for Emergency Mode
- Add /EMG/ST to codes for Self Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /DSI to codes for DSI Dimming

### Attachments

- Add /PIR to codes for Inbuilt PIR
- Add /WH to codes for White Bezel
- Add /CH to codes for Chrome Bezel
- Add /BA to codes for Brushed Aluminium Bezel

### LED Boards

All Luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

### Main Attributes

- Up to 120lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee
- CRI>80

## Catalogue Codes

Wattage	Cut-Out Size	Length	Width	Depth	Catalogue Code
10 W	95 mm	110 mm	110 mm	39 mm	SL/LED/1070/HAY/SQ/UGR19
18 W	170 mm	190 mm	190 mm	43.5 mm	SL/LED/2070/HAY/SQ/UGR19
25 W	210 mm	228 mm	228 mm	43.5 mm	SL/LED/3000/HAY/SQ/UGR19

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.