



Application

A unique range of fully adjustable recessed LED downlighters, suitable for wall washing and display lighting where high vertical illuminance levels are required.

Ideal for:

- Showrooms
- Atriums
- Double Height Areas

Body

1mm steel body finished in powder coat Silver. Internal luminaires enclosed in a UV glass lens, engraved with a decorative pattern. IP20 is achieved as standard. Each luminaire comes complete with a pre-wired gear box, with an option of a Plug and socket for ease of installation. A fully adjustable spring guarantees that aiming positions are maintained.

Sizes (nominal)

Cut Out Size
339 x 180
Bezel Size
348 x 189

Control Gear

Standard

Lamps

Using high output LED's we achieve outstanding efficiency values, up to 85 lm/w and a rated life of 50000 hours. Our optimized thermal management system ensures quality is maintained.



Catalogue Codes

Lamp Type	Length	Width	Depth	Catalogue Code
NA	348	189	145	SL/LED/5000/HAYLO/DBL
NA	348	189	145	SL/LED/4000/HAYLO/DBL
NA	348	189	145	SL/LED/3000/HAYLO/DBL

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.