



Application

A unique range of fully adjustable recessed LED downlighters, suitable for wall washing and display lighting. Ideal for Showrooms where high vertical illuminance levels are required.

Body

1mm steel body finished in powder coat Silver. Internal luminaires Enclosed in a UV glass lens, engraved with a decorative pattern. IP20 is achieved as standard. Each luminaire comes complete with a pre-wired gear box, with an option of a Plug and socket for ease of installation. A fully adjustable spring guarantees that aiming positions are maintained.

Sizes (nominal)

Length: 500 mm
Width: 195 mm
Depth: 162 mm
Cut Out: 495x180 mm

Control Gear

- StandardLED
- DALI DimmingLED
- DSI DimmingLED

Options Available

Add /EMG to codes for Emergency Mode

Attachments

Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 140lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- 5 YearGuarantee

Catalogue Codes

Lamp Type	Length	Width	Depth	Catalogue Code
24.0 W	500 mm	195 mm	162 mm	SL/LED/3300/HAYLO/TRP
34.2 W	500 mm	195 mm	162 mm	SL/LED/4800/HAYLO/TRP
46.0 W	500 mm	195 mm	162 mm	SL/LED/6360/HAYLO/TRP
66.0 W	500 mm	195 mm	162 mm	SL/LED/9300/HAYLO/TRP

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.