



Application

A compact High-Bay LED luminaire where emphasis has been placed on design and style.

The prismatic refractor by Lexalite achieves efficacy in excess of 90% and gives upward light and creates a bright overall project appearance.

Ideal for:

- Industrial areas
- Sports halls
- Shopping malls
- Showrooms
- Supermarkets

Body

Constructed from 1mm spun steel, finished in powder coat silver as standard.

A Decorative Prismatic Refractor gives efficient light distribution. Alternatively a Spun Aluminium Reflector is available for a more standard approach.

Sizes (nominal)

Large version: 480 mm diameter

Small version: 414 mm diameter

Control Gear

Standard

- High Frequency

Options Available

- High Frequency Digital Dimming
- Integrated PIR Daylight Control
- Emergency Mode

Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard.

Options are available from 3000k to 5000k.

All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Catalogue Codes

Wattage	Diameter	Depth	Catalogue Codes
24.4 W	414 mm	420 mm	SL/LED/2000/H-B/DEC
36.6 W	414 mm	420 mm	SL/LED/3000/H-B/DEC
38.8 W	414 mm	420 mm	SL/LED/3800/H-B/DEC
39.6 W	414 mm	420 mm	SL/LED/4000/H-B/DEC
62 W	414 mm	420 mm	SL/LED/5000/H-B/DEC

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.