



Application

Where decorative wall mounted fittings are required our Hydra LED offers exceptional performance and an IP65/IK10 rating. The Hydra offers combined direct/indirect light.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets
- Apartments
- Exterior Building Walls/Fascias

Body

Formed from 1mm Spun steel and finished in white as standard.

Sizes (nominal)

Length: 170 mm
Width: 140 mm
Depth: 59 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

Add /EMG to codes for Emergency Mode
Add /EMG/ST to codes for Self Test Emergency
Add /EMG/AD to codes for Addressable Emergency
Add /DALI to codes for DALI Dimming
Add /DSI to codes for DSI Dimming

Attachments

Add /PIR to codes for Inbuilt PIR

LED Boards

All luminaires are supplied with either 4300K or 5000K colour temperature. All performance DATA is taken at an ambient temperature of +25 Degrees Celsius.

Main Attributes

- Up to 82lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee
- CRI > 80

Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
8 W	170 mm	140 mm	59 mm	SL/LED/655/HYD/WM/UD

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.