



Application

Where decorative wall mounted fittings are required our Hydra LED Square offers exceptional performance and an IP65/IK10 rating. The Hydra offers combined direct/indirect light.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets
- Apartments
- Exterior Building Walls/Fascias

Body

Formed from 1mm Spun steel and finished in white as standard.

Sizes (nominal)

Length: 139 mm
Width: 115 mm
Depth: 52 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

Add /EMG to codes for Emergency Mode
Add /EMG/ST to codes for Self Test Emergency
Add /EMG/AD to codes for Addressable Emergency
Add /DALI to codes for DALI Dimming
Add /DSI to codes for DSI Dimming

Attachments

Add /PIR to codes for Inbuilt PIR

LED Boards

All luminaires are supplied with either 4300K or 5000K colour temperature. All performance DATA is taken at an ambient temperature of +25 Degrees Celsius.

Main Attributes

- Up to 82lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee
- CRI > 80

Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
8 W	139 mm	115 mm	52 mm	SL/LED/670/HYD/SQ/WM/UD

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.