



Application

A slim, stylish luminaire with a curved end profiles. Resisting dust and insects, it enjoys an IP44 protection rating thus reducing maintenance costs. The diffuser and end caps are manufactured in poly carbonate with stainless steel screws.

Ideal for:

- Schools
- School Corridors
- Health Care Buildings

Body

Formed from 1.0mm bright steel and finished in a high gloss electrostatic powder coat. A high output Micro-prism diffuser is used to maintain the High Output of the LED's located behind an opal diffuser.

Sizes (nominal)

Length: 600/1200/1500 mm
Width: 100 mm
Depth: 110 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED
- WI-FI

Options Available

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /DSI to codes for DSI Dimming
- Add /WI-FI to codes for Wireless Control

Attachments

- Add /PIR to codes for Inbuilt PIR

Lamps

All Luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 139lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee

Catalogue Codes

Wattage	Lumens	Length	Width	Depth	Catalogue Code
19.9 W	2731 lm	1210 mm	100 mm	110 mm	SL/LED/12/3290/JPT
24.4 W	3395 lm	1210 mm	100 mm	110 mm	SL/LED/12/4090/JPT
29.0 W	4050 lm	1210 mm	100 mm	110 mm	SL/LED/12/4880/JPT
32.0 W	4665 lm	1210 mm	100 mm	110 mm	SL/LED/12/5620/JPT
39.0 W	5246 lm	1210 mm	100 mm	110 mm	SL/LED/12/6320/JPT
44.0 W	5810 lm	1210 mm	100 mm	110 mm	SL/LED/12/7000/JPT
49.2 W	6325 lm	1210 mm	100 mm	110 mm	SL/LED/12/7620/JPT
30.0 W	4241 lm	1510 mm	100 mm	110 mm	SL/LED/15/5110/JPT
35.8 W	5063 lm	1510 mm	100 mm	110 mm	SL/LED/15/6100/JPT
42.0 W	5934 lm	1510 mm	100 mm	110 mm	SL/LED/15/7150/JPT
48.0 W	6557 lm	1510 mm	100 mm	110 mm	SL/LED/15/7900/JPT
54.5 W	7262 lm	1510 mm	100 mm	110 mm	SL/LED/15/8750/JPT
61.0 W	7909 lm	1510 mm	100 mm	110 mm	SL/LED/15/9530/JPT

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.