



Application

The Line Connect LED fitting is constructed from polycarbonate and is designed with high intensity LED emitters for a wider range of interior applications including shelf & cabinet illumination.

Body

Line Connect is constructed from a polycarbonate body and an acrylic diffuser.

Sizes (nominal)

- 267 mm
- 343 mm
- 603 mm
- 904 mm
- 1204 mm
- 1504 mm

Control Gear

Standard

Lamps

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
2 W	267 mm	22 mm	42 mm	SL/LED/3/210/L-C
4 W	343 mm	22 mm	42 mm	SL/LED/3/330/L-C
8 W	603 mm	22 mm	42 mm	SL/LED/3/710/L-C
12 W	904 mm	22 mm	42 mm	SL/LED/3/1184/L-C
17 W	1204 mm	22 mm	42 mm	SL/LED/3/1750/L-C
24 W	1504 mm	22 mm	42 mm	SL/LED/3/2150/L-C

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.