



Application

The Low-Cloud LED is an IP65 rated, high output industrial luminaire. The standard beam angle is 120° and the fitting has an IK08 rating.

Ideal for:

- Warehouses
- Car Dealerships
- Double Height Areas

Body

The fitting benefits from a light weight aluminium alloy body. Stainless steel screws are used to secure the poly-carbonate diffuser, giving the fitting its IP65 rating.

Sizes (nominal)

- 235 mm Diameter

Control Gear

Standard LED

Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 110lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Diameter	Depth	Catalogue Code
90.0 W	173 mm	260 mm	SL/LED/11500/L-C
150.0 W	173 mm	260 mm	SL/LED/17300/L-C
195.0 W	235 mm	260 mm	SL/LED/23000/L-C

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.