



Application

The Mezzina MKII is a high specification IP65 weatherproof, vandal resistant luminaire. A unique diffuser design is utilised to obtain optimum light output and distribution.

Ideal for:

- Staircases
- Corridors
- StoreCupboards
- ExternalAreas

Body

Formed from high impact, UVA stabilized polycarbonate. Body is round with 4 clips to hold the diffuser in.

Sizes (nominal)

- 350 mm
- 430 mm

Control Gear

Standard LED

Options Available

- High Frequency Digital Dimming
- Emergency Mode
- Inbuilt PIR

Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard.

Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

| Lamp Type | Diameter | Depth | Milliamp | Catalogue Code |
|-----------|----------|--------|----------|----------------------------|
| 12.0 W | 350 mm | 110 mm | 300 mA | SL/LED/1218/MEZ/MKII/300mA |
| 15.0 W | 350 mm | 110 mm | 375 mA | SL/LED/1521/MEZ/MKII/375mA |
| 18.0 W | 350 mm | 110 mm | 450 mA | SL/LED/1826/MEZ/MKII/450mA |
| 16.0 W | 430 mm | 110 mm | 400 mA | SL/LED/1622/MEZ/MKII/400mA |
| 19.0 W | 430 mm | 110 mm | 475 mA | SL/LED/1927/MEZ/MKII/475mA |
| 21.0 W | 430 mm | 110 mm | 525 mA | SL/LED/2130/MEZ/MKII/525mA |

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.