



Application

The Micro New-Age Continuous LED fitting is constructed from anodised aluminium and is designed with high intensity LED emitters for a wide range of interior applications including shelf & cabinet illumination. Supplied with mounting clips for ease of installation.

Body

Extruded Aluminium body with a choice of clear or Micro-prism diffusers.
An IP65 rating is available as an option for this fitting.

Sizes (nominal)

- 130 mm
- 500 mm
- 900 mm
- 1000 mm
- 1400 mm

Overall Lengths may be specified in increments of 80 mm subject to MOQ.

Control Gear

Standard LED

Options Available

- RGB ColourChoice
- White Temperature ColourChoice
- Micro-prismLens
- ClearLens
- IP65Rating

Lighting Control

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- Up to 115lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- 5 YearGuarantee

Catalogue Codes

Wattage	Length	Width	Depth	Milliamp	Catalogue Code
2.4 W	130 mm	18 mm	8 mm	50 mA	SL/LED/250/MICRO/N-A/CON
10.8 W	500 mm	18 mm	8 mm	50 mA	SL/LED/1200/MICRO/N-A/CON
20.4 W	900 mm	18 mm	8 mm	50 mA	SL/LED/2300/MICRO/N-A/CON
22.8 W	1000 mm	18 mm	8 mm	50 mA	SL/LED/2500/MICRO/N-A/CON
32.4 w	1400 mm	18 mm	8 mm	50 mA	SL/LED/3700/MICRO/N-A/CON

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.