



Application

The Mini Spot range offers simple and effective emergency lighting from attractive high intensity projectors. More suitable for areas with aesthetic concerns than conventional twin projector floodlights these units are ideal for a wide range of applications requiring open area illumination.

Ideal for:

- Car Showrooms
- Atrium Office Areas
- Large Open High Areas

Body

Constructed from Polycarbonate

Sizes (nominal)

Height: 108mm

Width: 186mm

Depth: 55mm

Lighting Control

All Luminaires are supplied with colour 840, 4000k LED's as standard.

Options are available from 3000k to 5000k.

All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- 2 Watt LED 6000k Lamp
- Designed to comply with EN60598:2:22
- Self Test versions available
- Addressable versions available

Catalogue Codes

Wattage	Height	Width	Depth	Cat No.
3.6 W	108 mm	186 mm	55 mm	SL/LED/MSS/M3
3.6 W	108 mm	186 mm	55 mm	SL/LED/MSF/M3
7.2 W	108 mm	186 mm	55 mm	SL/LED/MTS/M3
7.2 W	108 mm	186 mm	55 mm	SL/LED/MTF/M3

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.